Fabry-Pérot Laser Diodes (FP): High-Power Option



WAVELENGTH

760–840 nm
840–1100 nm
1100–1700 nm
1700–2400 nm
2400–2900 nm
2800–6500 nm
6000–14000 nm

High-Power OPT

RED COALS

ISO


9001

14001

nanoplus FPs are specially designed and characterized to fit your requirements. For more than 20 years, nanoplus has been manufacturing DFB and FP lasers with excellent performance. Our devices operate **reliably** in more than 30,000 installations worldwide.

Key features:

- BROADBAND
- HIGH-POWER
- SMALL FOOTPRINT



Any **custom wavelength** is possible: You tell us what you need! With our outstanding technology we design any wavelength **between 760 nm and 2900 nm** with an accuracy of +/- 20 nm.

The **output power** of **several mW** yields a strong signal and gives large flexibility to your application. High power up to 1 W for diverse applications is available on request.

We offer **various packaging options**, e. g. several free space housings including TEC and NTC, fiber coupling, **collimation** and **custom designs**. What are your requirements?

Long-term stability is one of the principal features customers value about our lasers! Even in **harsh environments** nanoplus devices perform excellently – low maintenance warranted.

"Do not change your ideas, let us deliver a laser that fits your application."

If you require **custom specifications**, please contact us. Nearly 80 % of our devices are more or less customerspecific. As nanoplus is a **fully vertically integrated company**, we control the entire process chain from design to packaging. Both nanoplus production facilities are based in **Germany**. To guarantee consistent product quality we apply a strict and **ISO certified quality management system** at all levels.

Our sales and R&D teams have long-standing experience in developing lasers. They will be pleased to provide advice at any time - rely on us from design stage to product realization as well as after-sales:

We make market leaders!




nanoplus high-power Fabry-Pérot laser on submount with AIN carrier



Typical Specifications: High-Power Option

This data sheet reports performance data of a **sample High-Power Fabry Pérot Laser at 2145 nm**, which is representative for all wavelengths between 1950 nm and 2350 nm with **high-power option**. For standard specifications with less power, please refer to our low power section: <u>http://www.nanoplus-usa.com/products/FP</u>.



Typical room temperature cw spectrum of Typical PI and VI curve a nanoplus HPFP laser at 2145 nm of a nanoplus HPFP laser at 2145 nm symbol electro-optical characteristics unit min. typ max. -20 operating wavelength (at T_{on}, I_{on}) please specify +20 λ_{op} nm P_{op} optical output power (at λ_{op}) mW 1000 operating current I_{op} mΑ 5000 operating voltage V_{op} V 2.5 threshold current I_{th} mΑ 300 operating chip temperature T °C +15 +20 +40 storage temperature* T_s °C -40 +20 +80


laser packaging options

Rev.HPFP2145.03

* non condensing

submount with AIN carrier, without TEC, without NTC

Technical drawings & accessories are available at: <u>https://www.nanoplus-usa.com/products/packaging</u>



Please contact <u>victor.perez@nanoplus.com</u> for customized specifications, quotes and further questions. Visit the <u>nanoplus website</u> for technical notes, application samples or literature referrals.

nanoplus America Inc., nanoplus-usa.com, phone: +1-720-453-2454, email: victor.perez@nanoplus.com [©]copyright nanoplus America Inc. 2024, all rights reserved. Technical data is subject to change without notice.